




TAKE A LOOK AT THE BEST WHEEL GEARBOX IN THE INDUSTRY AND ITS 10-YEAR/10,000-HOUR WARRANTY


EVERY DETAIL HAS BEEN ENGINEERED THROUGH THOUGHT AND KNOWLEDGE FOR A POWERFULLY BUILT GEARBOX

1. Stainless steel diaphragm cover provides years of corrosion-free life
2. The largest input bearings in the industry provide 55 percent greater load capacity for today's larger tires and faster rotation times
3. Polished, high-strength worm gear with dual input shafts eliminates the need to stock lefts and rights
4. Seal protector blocks out contaminants and extends seal life
5. Unique rolling diaphragm design minimizes pressure build-up during operation. Relieving negative pressure prevents water and contaminants from being drawn into the gear case.
6. Centering ring doubles as a load-bearing surface, relieving stress on the lug bolts and lessening potential wheel damage
7. Large 2 1/4-inch diameter output shaft and flange made of high-strength steel to handle tower loads
8. Cartridge style input and output seals utilize a multi-lip design and precision ground, polished sealing surface to eliminate oil leaks
9. Reinforced housing provides more material in high stress areas, increasing overall strength on the gearbox. Multi-bolt mounting pattern fits all brands
10. End cap is machined from cast steel to handle the higher loads from larger tires
11. Input shaft cover protects against seal and shaft damage
12. Non-seizing drain and fill plug for easy maintenance
13. New bull gear, designed for greater tooth contact, resulting in higher load capacity and longer life
14. Dual input shafts allow for universal mounting on either end of tower base



SPRINKLER LUBE® 1200

Save hundreds on gearbox oil (not to mention down time) with proper maintenance and Sprinkler Lube® from Reinke.



TOWABLE GEARBOX

Like the non-towable version, it also has a 10-year/10,000-hour warranty and possesses the same high quality features and components.

THE REINKE CENTER DRIVE YEARS OF TROUBLE-FREE SERVICE



A high efficiency gear motor delivers exceptional torque to propel your system over the roughest terrain and through difficult soil conditions. Specifically designed and built for the demands of mechanized irrigation.

- 8-year, 8,000-hour warranty
- Helical Gear Design – 95% efficiency
- All aluminum gear case and motor housing assures cooler running, longer life and increased corrosion resistance
- Multi-bolt mounting pattern fits all brands
- High-strength steel shafting provides long life and dependability
- Thermally protected with automatic reset
- Heat-treated gears
- Specially designed input and output seals
- Top fill plug positioned to set correct oil level
- All critical electrical connections are encapsulated to resist moisture penetration
- C.S.A. and UL approved
- Stainless steel junction box cover
- Dual shaft seals
- New high capacity outer motor bearing
- 3 Output RPMs
Low 60:1 ratio or 29 RPM
Standard 40:1 ratio or 43 RPM
High 25:1 ratio or 70 RPM