

# BBI CRICKET AG & TURF



**Ideal for:** Fertilizer or Lime / Golf Courses, Turf, Sod, Food Plots and Small Farms / Can be pulled with low HP tractor / Ground Wheel Drive Conveyor / PTO or Hydraulic Driven Spinners

## BBI Cricket Ag & Turf

The BBI Cricket Ag and Turf is a fertilizer and lime spreader designed for precision dry material application. This spreader only requires a 30 to 40 horsepower tractor to pull it. The narrow wheel track width allows it to be maneuvered through narrow paths, while the wide flotation tires are standard to minimize compaction. Wide flotation tires are standard to minimize compaction.

## Unique Features

- Can be pulled with a low horsepower tractor (30 - 40 horsepower)
- External ground wheel driven by traction against the tire
- Ground wheel driven stainless steel mesh chain
- 24 inch dished spinner design for precision coverage
- 15 inch ground clearance
- Flotation tire and turf tire options minimize compaction

## BBI Cricket Ag & Turf Specifications Fertilizer / Lime

Working Width	Hydraulic - Fertilizer 80 feet, Lime 60 feet PTO - Fertilizer 60 feet, Lime 60 feet
Size	8 feet
Capacity (struck)	Standard: 64 cubic feet, struck 15 inch ground clearance
Hopper Material	Optional: 304 Stainless Steel Optional: Painted 409 Stainless Steel
Drive	Standard: Conveyor Ground Wheel Drive Standard: Manual Hydraulics to Engage Ground Wheel Optional: Conveyor & Spinner Ground Wheel Drive
Conveyor Chain	Standard: 16 inch 304 Stainless Steel Mesh Chain Optional: 16 inch Bar Chain in Lieu of Mesh
Press Wheel	Standard: Pneumatic Press Wheel Optional: Metal Press Wheel
Spinner Drive	Standard: PTO (540 RPM) driven Spinners (twin 24 inch spinners) Standard: PTO (1000 RPM) driven Spinners (twin 24 inch spinners) Optional: Hydraulic Spinners (Plug-to-Tractor) w/ ELIMINATOR Manifold
Tires & Suspension	Standard: 12,000 lb rigid single-axle 16.5 x 16.1 10 ply tires. W16C x 16.1 Ag type wheels, 8-Bolt hubs.
PTO Drive Line / CV Joint	Standard: 540 RPM Series 6 CV Joint PTO Shaft Standard: 1000 RPM Series 6 CV 1 3/4 20 Spline Standard: 1000 RPM Series 6 CV 1 3/8 21 Spline
Hopper Extensions	Standard: None Optional: 8 inch Unit Extension Brackets ONLY (without wood) Optional: 8 inch Unit 2 inch x 6 inch Extension Brackets with wood
Tarp	Standard: None Optional: 8 foot Box Type Tarp w Bow (Vinyl)