

CRUSTBUSTER

The Crustbuster Pays For Itself With Big Labor Savings & Increased Production!



**Built for high performance,
low maintenance**

**Attaches to Standard Class II
3-Point Tractor Hitch- No
Special Equipment required**



***LEWIS BROTHERS
MANUFACTURING INC.***

Total Hydraulic Operation. Pump Mounts Securely to the Tractor PTO Output Shaft

Less maintenance required than shaft type designs, and much safer

Cutting Blade design helps control depth of operation

Bolt-on tines for fast and simple replacement

Heavy Duty Construction

Breaks up cake material and conditions Litter

Removes moisture and reduces ammonia.



LEWIS CRUSTBUSTER

SPECIFICATIONS

- | | |
|---------------------------------|---------------------------------|
| • Width-----89-1/2" | • Hyd. Pressure @ 540 RPM— |
| • Length-----27" | 2200PSI |
| • Weight-----920 lbs | • Oil Type-----AW68 |
| • Throat-----84" | • Tank Capacity-----14 gal. |
| • PTO Hydraulic Pump-----15 gpm | • Tractor HP Required-----45 HP |

DEPENDABLE * SAVES TIME * SAVES MONEY * EASY-TO-OPERATE * LOW MAINTENANCE

LEWIS BROTHERS MANUFACTURING INC.

P.O. Box 146 * Baxley Ga. 31513 * (912) 367-4651 * Fax: (912) 367-3958

E-mail: sales@lbmfg.com * www.lbmfg.com